

# TECHNICAL DATA SHEET



**Product code:** 5298

**Sector:** Industrial

**Issue No:** 3

**Issue Date:** 28/10/24

## DELTA 000EP

Lithium based semi-fluid grease with extreme pressure (EP)

### Application

Use as received for centralised lubrication systems requiring a semi-fluid grease.

### Features & Benefits

- Adhesive properties.
- Good pumpability.
- Resistant to Water.
- High degree of corrosion protection.

### Typical Characteristics

Appearance	Dark Brown Smooth Semi-Fluid Grease
NLGI Classification	000
Thickener	Lithium Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	445 to 475
Drop Point (IP132) °C	n/a
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	00:00
Four Ball Weld Load (IP239)	315kgs
Timken OK Load (IP326)	23kgs (50lbs)
Operating Temperature Range °C	-30 to +110

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)