

DEWATERING FLUID 1782

Page: 1

Compilation date: 09/07/2008

Revision date: 06/06/2017

Revision No: 1b

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DEWATERING FLUID 1782

Product code: 5406

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: De-watering fluid

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd

Hillside Oilworks Rastrick Common

Brighouse

West Yorkshire

HD6 3DP

United Kingdom

Tel: +44 (0)1484 713201

Fax: +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; STOT RE 1: H372; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT

SE 3: H336

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause

drowsiness or dizziness. Causes damage to organs through prolonged or repeated

exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

DEWATERING FLUID 1782

Page: 2

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P273: Avoid release to the environment.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9-12, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-857-5	-	-	Flam. Liq. 3: H226; STOT SE 3: H336;	70-90%
			Asp. Tox. 1: H304; -: EUH066	

HYDROCARBON WAXES (PETROLEUM), OXIDIZED

DEWATERING FLUID 1782

Page: 3

2-(2-HEPTADEC-8-ENYL-2-IMIDAZOLIN-1-YL)ETHANOL - REACH registered number(s): 01-2119777867-13-XXXX

202-414-9	95-38-5	-	Acute Tox. 4: H302; Skin Corr. 1C:	<1%
			H314; STOT RE 2: H373; Aquatic	
			Acute 1: H400; Aquatic Chronic 1:	
			H410	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: Inhalation of vapours may cause irritation of nose, throat and airway.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: In all cases of doubt, or when symptoms persist, seek medical attention.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

[cont...]

DEWATERING FLUID 1782

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: Brown

Odour: Characteristic odour

Evaporation rate: Slow

DEWATERING FLUID 1782

Page: 5

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 2cSt

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 40 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.81 **pH:** No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-(2-HEPTADEC-8-ENYL-2-IMIDAZOLIN-1-YL)ETHANOL

ORAL	D 4 T	1.050	4 005	/1	
ORAI	∣ RA I	LD50	1.265	mg/kg	
	1 1 1 1 1				

DEWATERING FLUID 1782

Page: 6

Relevant hazards for substance:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: Inhalation of vapours may cause irritation of nose, throat and airway.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2-(2-HEPTADEC-8-ENYL-2-IMIDAZOLIN-1-YL)ETHANOL

ZEBRAFISH (Brachydanio rerio)	96H LC50	0.3	ma/l
ZEDITALIOLI (DIAGNYGANIO TENO)	3011 2000	0.5	1119/1

12.2. Persistence and degradability

Persistence and degradability: Expected to be inherently biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

DEWATERING FLUID 1782

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(Contains: Hydrocarbons, C9-12, m-alkanes, isoalkanes, cyclics, (2-25%), aromatics.)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H314: Causes severe skin burns and eye damage.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs <or state all organs affected, if known> through

prolonged or repeated exposure <state route of exposure if it is conclusively proven that

DEWATERING FLUID 1782

Page: 8

no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.