

# TECHNICAL DATA SHEET



Product code: 5497

Sector: Industrial

Issue No: 2

Issue Date: 30/06/22

## MILLERCARE AF

A blend of surface active polymers for use in water soluble metalworking fluids and associated industrial fluids.

### Application

Use as received as a tank side treatment between 0.01% and 0.02% depending on severity of foam. The antifoam should be added to the slow moving areas of the coolant system. Add the required antifoam and allow system to respond to the addition before adding any more.

Over dosing with antifoam can be counterproductive, so little and often is the preferred method.

### Features & Benefits

- Good foam control at low dilution rates.
- Low residue formation
- Non-silicone, no adverse effect on finishing process.

### Typical Characteristics

Density @ 20°C, g/ml	1
Solubility in Water	Dispersible
Appearance	Off White liquid

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)



**MADE IN BRITAIN**

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)