# **TECHNICAL DATA SHEET**



# PRODUCT NAME/VISCOSITIES:

# **MILLICLEAN 6211**

| Product No | 6211     |
|------------|----------|
| Issue No.  | 3        |
| Issue Date | 15/04/19 |

#### **DESCRIPTION:**

Milliclean 6211 is a high performance, alkaline cleaning and de-burring solution.

#### **APPLICATION:**

Suitable for cleaning ferrous and copper based metals, ultrasonic, spray and dip applications. Vibratory, de-burring systems.

Use typically at 2%, with a maximum temperature of 70°C.

Note: Not suitable for use on aluminum based metals. Product should be stored under cover. Avoid extremes of temperature and protect from frost.

#### **USER BENEFITS:**

- Multipurpose product.
- Low foaming.
- Effective even in hard waters.
- Nitrite free corrosion inhibitors, to prevent inter-operational rust problems.
- Inhibited to prevent staining of copper based metals.

# **TYPICAL CHARACTERISTICS:**

Specific Gravity @ 15°C 1.03
Kinematic Viscosity @ 40°C 7.0cSt
Flashpoint °C 100
pH @ 5% 10.00
Refractive Index Factor x 2.78

# **HEALTH AND SAFETY:**

Health and Safety Data Sheet 6211 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk







