

# TECHNICAL DATA SHEET



Product code: 5401

Sector: Industrial

Issue No: 3

Issue Date: 11/04/22

## RUST PREVENTIVE 1403

A light greasy rust preventative in a hydrocarbon solvent base with good de-watering properties.

### Application

Use as received for short term rust preventative on small machined parts.  
Apply by brushing, dipping or spray.

### Features & Benefits

- Very good de-watering capabilities
- Lubricant and corrosion protection properties
- Up to 3 months' indoor protection
- Very searching giving a thin even coating
- Economical in use
- Easily removal with everyday solvents such as white spirit

### Typical Characteristics

Density @ 15°C, g/ml	0.811
Kinematic Viscosity @ 40°C, cSt	2.0
Flashpoint, °C	40
Film Thickness, µm	1.8
Coverage, m <sup>2</sup> /litre	66
Indoor Protection	up to 3 months

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)



**MADE IN BRITAIN**

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

# TECHNICAL DATA SHEET



**MADE IN BRITAIN** 

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)