TECHNICAL DATA SHEET



Product code: 5488 Sector: Automotive (Passenger car & LCV) Issue No: 3 Issue Date: 17/01/23

LHM Plus

Mineral based hydraulic fluid

Application

A green mineral-based oil specifically designed for use in power steering, suspension, hydraulic and braking systems.

Suitable for

Passenger Car and Light Commercial Vehicle (LCV)

ISO 7308

Ford ESN, M6C 59A PSA B71 2710

PSA Group Inc. Peugeot, Citroen, DS, Bentley, Rolls Royce

Typical Characteristics

Density @ 15 °C, g/ml	0.845
Kinematic Viscosity @ 100 °C, cSt	6.4
Pour Point, °C	-54
Flash Point, °C	122
Colour	Greer

Features & Benefits

- Excellent lubricating properties across both hot and cold temperature conditions.
- High boiling temperature and insensitive to moisture (non-hygroscopic product).
- Provides anti-corrosion, anti-wear and contains anti-foam additives.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: Warning: Suitable for use only in hydraulic systems using a green mineral oil.

Please be sure to check the vehicle handbook. Only fill this fluid into hydraulic reservoirs painted green. Never use this fluid in any reservoirs painted black. Not to be used in vehicles using vegetable based fluid or synthetic hydraulic oil.







