

TECHNICAL DATA SHEET



Product code: 7631 **Sector:** Automotive (Passenger car & LCV)

Issue No: 3 **Issue Date:** 17/01/23

Central Hydraulic Fluid (CHF)

Multifunctional hydraulic fluid developed for modern automotive applications.

Application

Recommended for use in the following applications: power steering, suspension level control, hydro pneumatic control, active stability control, shock absorbers (dampers), traction control, cabriolet electronic roof mechanism, central locking etc.

Suitable for

Passenger Car and Light Commercial Vehicle (LCV)

PSA S71 2710 (LDS)

BMW, Brabus, Chrysler, Dodge, Ford,
GM, Jeep, Mercedes-Benz, Mini, Mopar, Opel, Saab,
Saturn, Volvo,
PSA Inc Peugeot, Citroen, DS,
VWAG Inc. VW, Audi, Seat, Skoda, Bentley,
Porsche, Lamborghini

Typical Characteristics

Density @ 15°C, g/ml	0.850
Kinematic Viscosity @ 100°C, cSt	7.0
Flash Point, °C	>140
Pour Point, °C	-48

Features & Benefits

- A long-life hydraulic fluid with outstanding performance for modern vehicles.
- Provides protection to highly loaded hydraulic pumps.
- Operational noise reduced at cold climate conditions.
- Excellent anti-corrosion, anti-wear and anti-foam additives.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: Not suitable for automatic transmission systems.



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk